

SINISTER DIESEL



AR EXHAUST TIP

AR Exhaust Tip

A



PACKING LIST:

<u>Part#</u>	<u>QTY.</u>	<u>Description</u>
A	1	AR Exhaust Tip (includes clamping bolt)

Read all instructions prior to install.

Note: Prior to installation, please compare the parts that you have received with the bill of materials provided on this page to assure that you have all the parts necessary for the installation.



CAUTION!!! Never work on a hot vehicle. Serious injury in the form of burns can result if the vehicle has been in use. Allow vehicle to cool prior to installation. Always wear eye protection when working on or under any vehicle.

Step 1: Remove any existing exhaust tip that may obstruct the installation of the new Sinister AR Exhaust Tip.

(Image 1)



(Image 1)

Step 2: The existing exhaust pipe may have to be shortened to accommodate the extra length of the new AR Exhaust Tip. *(Image 2)*

Note: Your exhaust pipe may not be removable as show in Image 2. In this case you may cut the exhaust pipe to length without removal.

Cut exhaust pipe to desired length



(Image 2)

Step 3: Place and position the new AR Exhaust Tip to your desired location. Tighten the clamping bolt tight to ensure the exhaust tip is secure. *(Image 3)*



(Image 3)





2025 Opportunity Dr.
Roseville CA, 95678
877-692-4110 - SinisterDiesel.com